

 **Met One Instruments, Inc.**

BAM 1022 Real-Time Portable, Beta Attenuation Mass Monitor

Met One Instruments, Inc. BAM 1022, Real-Time Portable Beta Attenuation Mass Monitor, continuously measures the mass concentration of ambient particulate matter collected onto glass filter tape with time resolution of one-minute.

The BAM 1022 employs an in-line sampling geometry in which the attenuation of beta rays across filter media is measured and particulate matter is sampled simultaneously. This allows ambient sampling to occur for virtually 60 minutes each hour. It also allows for beta ray measurements to be made for virtually the entire hour thereby improving sensitivity and time resolution.

The BAM 1022 employs a unique "in-situ" sampling technique where the beta measurement is kept at a near fixed temperature above ambient conditions, thereby minimizing measurement error due to loss of semivolatile particulate material or due to excessive moisture in the sample stream. Highly accurate measurements are made without having to employ expensive Nafion dryers thereby increasing reliability and decreasing operating costs. The integrated shelter does not employ air conditioning, nor does the sampling system employ flow splitters. This results in easier service, enhanced reliability and lower power consumption.

The BAM 1022 comes integrated into its own lightweight enclosure with easily detachable pump box making it ideal for installation in areas where no permanent structure or walk-in shelter is available. Power consumption is modest as no air conditioning is required. No component weighs more than 40 lb. (18K) meaning that it is easily transportable by one person. The entire system may be set up and put into operation in less than ten minutes.



The BAM 1022 offers the following advanced features:

- In-Situ measurement of PM that provides high accuracy, minimal measurement artifacts.
- Reduced background determination frequency.
- Unsurpassed performance under high ambient dew point operation.
- Advanced communications features allowing remote operation and cloud-based communication.
- Advanced diagnostics.
- Improved sensitivity compared to other in-line beta attenuation mass monitors.
- Meteorological and other sensor inputs.

Applications: The BAM 1022 has US-EPA designation for PM_{2.5} (EQPM-1013-209) for which a dedicated hourly output channel is available. A second, real-time output channel will provide the user with continuous PM updates down to 1-minute time resolution. The BAM 1022 is ideal for the following applications:

- **Criteria-Grade Air Quality Surveillance Networks**
- **Near-Roadside PM Monitoring**
- **Rapid-Deployment Applications**
- **Research and Development**



Specifications

BAM 1022 BETA ATTENUATION MASS MONITOR

Parameter

Measurement Principle:	Beta Attenuation.
US EPA Designations:	PM _{2.5} EPA Class III Federal Equivalent Method (EQPM-1013-209)
Accuracy:	Meets US-EPA Requirements for Class III PM _{2.5} FEM
Sampling Time:	Continuous Air Sampling with Hourly Tape Advance
Measurement Cycles:	Primary: Automatic Hourly PM Measurement (Required for PM _{2.5} FEM Operation) Secondary: User Selectable Short Term Averages (1, 5, 10, 15, or 30 minute)
Sample Flow Rate:	16.7 liters/minute
Filter Tape:	Continuous glass fiber filter, 30mm x 21m roll. Up to 2 months operation per roll.
Maintenance Interval:	8 Weeks (minimum)
Span Check:	Manual Audits Performed with Zero and Span Foils (Included)
Beta Source:	¹⁴ C (carbon-14), 60 µCi ±15 µCi (2.22 MBq)
Detector Type:	Scintillation Photomultiplier Tube.
Operating Temperature Range:	-30° to +50° C
Operating Humidity Range:	0 to 90% RH, non-condensing
Enclosure:	Instrument is integrated into its own weatherproof enclosure and sits on a separable, pump box
Analog Output:	Two channels; optically isolated; switch settable voltage or current 0-1, 0-2.5, 0-5 VDC / 0-20, 2-20, 4-20 mA (Hourly Concentration and/or or User Selectable Short Term Average)
Serial Interfaces:	1 channel; full duplex RS-232, USB, and Ethernet serial (Shared common serial output). Baud rates 1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200
Compatible Software:	COMET™ (included), Air Plus™, terminal programs such as HyperTerminal®
Data Logger Memory:	11,827 records (1.4 years @ 1 record/hr. 8 days @ 1 record/min).
Alarm Contact Closure:	1 Channel; dry no contact; 1A at 125 VAC or 60 VDC Minimum
Power Supply:	100 - 230 VAC; 50/60 Hz universal AC power
Power Consumption:	300W (Incl. BAM-1022, Inlet Heater, BX-126 or BX-127 Pump, and Vent Fan)
Approvals:	NRC, ISO-9001, ROHS, US-EPA <i>Specifications are subject to change at any time.</i>

