

## Analytical Industries Inc.

2855 Metropolitan Place, Pomona, CA 91767 USA ♦ Tel: 909-392-6900, Fax: 909-392-6900, e-mail: sales-medical@aii1.com,Website: www.aii1.com

Oxygen Sensor Model	GPR-12-333-MH	i	
Measuring Range	0-100% O2	i	
Signal Output (1)	0-100% O2 590-950 μA		
Response Time 90%	3 Seconds		
Accuracy Full Scale (2)	<u>+</u> 1%		
Accuracy FS Over Operating Range (3)	<u>+</u> 5%		//
Drift % Signal Month (2)	< 1%		
Linearity (2)	<u>+</u> 1%		
Humidity Non-Condensing	0-99% RH		
Temperature Coefficient	2.54% / C	141 / V 1	WJL
Operating Temperature	0-45° C	M16 X 1 THREADS——	_
Operating Pressure	Constant 5-30 PSIG		
Flow Rate	.1-10 LPM		
Expected Life (1)	12-24 Months		
Storage (4)	0 to 40°C		
Warranty (5)	12 Months		
Electrical Connections	4 Pin Molex		
Packaging	Anti-Static Bag in 3" x 3" x 1.5" paper box		
Recommended Storage	< 6 months		

- (1) In air @ 25° C and 1 atm. Expected life varies inversely with changes in O2 concentration, temperature, pressure. PPM Sensors Expected life based on < 1000 PPM
- (2) Under constant conditions. Calibrate as near sample conditions as possible. Sensing surface should point downward.
- (3) Once the signal output stabilizes following a step change in temperature.
- (4) Recommended 0-40° C. Sensors may be stored at -10 to 55° C on an intermittent basis only.
- (5) Ex-factory unless agreed to in writing. Under normal application conditions sensor is warranted to be free of defects in material and workmanship for the period specified above provided the sensor is properly installed and operated. Analytical Industries Inc. shall not be liable for buyer's negligence, misapplication, alteration or abuse. The sole remedy for a sensor determined to be defective by Analytical Industries Inc. is limited to replacing the defective sensor.