



# QE25SP-S-MT-D0

Pyroelectric detector for laser energy measurement up to 3.0 J.



## PRODUCT FAMILY KEY FEATURES

### MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

### LOW NOISE LEVEL

2 µJ for the MB coating

### QED ATTENUATOR AVAILABLE

Measure up to 5X higher energies. Available with optional calibration, all wavelengths between 532 & 1064 nm, or single wavelength. [Read more.](#)

### HIGH REPETITION RATE OPTIONS

- QE25HR-MB: 1 000 Hz
- QE25HR-MT: 10 000 Hz

### TEST TARGET INCLUDED

With the MB models

### SMART INTERFACE

Containing all the calibration data

### COMPATIBLE STAND

[STAND-D-233](#)

## SPECIFICATIONS

### MEASUREMENT CAPABILITIES

Spectral range <sup>1</sup>	0.193 - 20 µm
Typical rise time	20 µs
Repeatability	<0.5%
Maximum repetition frequency <sup>2</sup>	6000 Hz
Maximum measurable energy <sup>3</sup>	3 J
Noise equivalent energy <sup>4</sup>	2 µJ
Maximum pulse width	10 µs
Energy calibration uncertainty	±3 %

1. For the calibrated spectral range, see the user manual.  
2. May be limited by the display or PC interface. Please refer to the corresponding user manual.  
3. At 1064 nm, 7 ns, 10 Hz. Increasing pulse width increases maximum measurable energy.  
4. Nominal value. Actual value depends on electrical noise in the measurement system.

### DAMAGE THRESHOLDS

Maximum average power density <sup>1</sup>	10 W/cm²
Maximum energy density <sup>2</sup>	0.5 J/cm²
Maximum power	5 W

1. May vary with wavelength and average power.  
2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

### PHYSICAL CHARACTERISTICS

Cooling	Convection
Aperture width	25 mm
Aperture height	25 mm
Absorber	MT
Dimensions	50H x 50W x 14D mm
Weight	0.12 kg



ORDERING INFORMATION

QE25SP-S-MT-D0	200460
QE25SP-S-MT-INT-D0	202385

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at [gentec-eo.com/contact-us](http://gentec-eo.com/contact-us)