





Position Sensing Water-Cooled Thermopile Sensors **FEATURES** to 5 kW

Sensors Useful for Non-Visible Beams

These unique position sensing thermopiles display the position of the incident beam on the sensor disk,in addition to measuring power when used with the LabMax and LabMax-Pro meters. This information allows the user to safely and precisely align the sensor and the beam being measured. This is particularly useful for non-visible beams.

Water-cooling and careful thermal management within these sensors enable them to deliver the ultimate in high power handling capacity. They can capably measure industrial CO₂ and Nd:YAG lasers at power levels up to 5 kW.





- 100 W to 5000 W range
- Broadband coatings
- 0.25 to 10.6 µm spectral range
- Compact water-cooled design
- · Large 38 mm or 55 mm diameter aperture
- Excellent for high-power CO₂ and Nd:YAG lasers

APPLICATIONS

- Medical
- Scientific
- Industrial
- · General Laser Power Measurement to 5kW






Position Sensing Water-Cooled Thermopile Sensors to 5 kW Datasheet

SPECIFICATIONS	BeamFinder	LM-1000	LM-2500	LM-5000	
Wavelength Range (µm)	0.3 to 10.6		0.25 to 10.6		
Power Range (W)	100 to 1000 100		100 to 2500	100 to 5000	
Resolution (W)	1				
Maximum Power Density ¹ (kW/cm ²)	1 to 2.5				
Maximum Energy Density (mJ/cm ²)	600, 1064 nm, 10 ns				
Detector Coating	Broadband				
Active Area Diameter (mm)	35	38	56		
Calibration Uncertainty (%) (k=2)	±5				
Calibration Wavelength (nm)	10.6				
Cooling Method	Water-cooled				
Cable Type	LM DB-25				
Cable Length (m)	6				
Part Number	1098427	1098409	1098437	1098421	


¹ The damage resistance of the coating is dependent upon the beam size and profile, the average power level, and the water flow rate. Contact Coherent or your local representative for details related to your application.

MECHANICAL SPECIFICATIONS


BeamFinder



LM-1000



LM-2500/LM-5000





Coherent, Inc., 5100 Patrick Henry Drive Santa Clara, CA 95054 p. (800) 527-3786 | (408) 764-4983 f. (408) 764-4646

tech.sales@coherent.com www.coherent.com